

## MULTIUSOS

### Silicone sealant with fungus protection Acetic System.

#### 1. DESCRIPTION

Silicone sealant with fungus protection ready for use with a standard or pneumatic gun. Its curing process occurs when coming into contact with atmospheric humidity, becoming a permanently elastic mass, with extraordinary resistance to weathering, aging and atmospheric agents, as well as excellent performance when confronted with chemical agents. Good adhesion on glass, aluminium, ceramics, tiles and non-porous materials in general. This silicone contains the biocide product carbendazime with fungicide properties.

#### 2. APPLICATIONS

It is appropriate for sealing a wide range of joints in plumbing, construction and sanitary applications.

#### 3. SPECIFICATIONS

DELIVERY FORM:		CURED:	
Specific weight:	0,93 - 0,95 gr/ml	Modulus at 100% <sup>(2)</sup> :	0,25 - 0,40 N/mm <sup>2</sup>
Odour:	Acetic acid	Tensile strength <sup>(2)</sup> :	min. 1,1 N/mm <sup>2</sup>
Consistency:	Thixotropic paste	Breakage elongation <sup>(2)</sup> :	min. 400 %
Application temperature:	-10 +35 °C	Hardness Shore A <sup>(3)</sup> :	10 - 15
Tack-free: <sup>(1)</sup>	6 minutes	Temperature resistance:	-50 +150 °C.
Easy to extrude		Can not be repainted	

<sup>(1)</sup>LMO-22, quality internal method at Collak. <sup>(2)</sup>DIN 53504, S2. <sup>(3)</sup>DIN 53505.

#### 4. INSTRUCTIONS FOR USE

Cut the conical tip of the cartridge, screw on the nozzle and cut to required size. Insert the cartridge into applicator gun, extrude the silicone in a continuous strand over the whole surface of the joint, avoiding to form air pockets. All surfaces to be sealed should be totally consistent, clean and dry.

#### 5. PACKING

Colours: Translucent and white  
In 280 ml cartridges (25 cartridges / carton).

#### 6. STORAGE

Store in a cool, dry place at +5 to +35 °C. Under these conditions the silicone retains its original properties for at least one year.

#### 7. CAUTIONS

During the curing process avoid contact with the eyes, mouth etc. Wash the hands after use. Once cured, this sealant becomes a totally non-toxic product. Keep out of reach of children

Every endeavour has been made to ensure that the information given herein is true and reliable, but is given only for the guidance of our customers. Collak, S.A. cannot accept any responsibility for loss or damage or infringement of patent rights, that may result from the use of the information, due the possibility of variations of processing or working conditions are outside our control. Users are advised the confirm the suitability of the products with their own tests.  
We put at your service our technical service for any conference or explanation.